





Dimensions subject to change without notice.

Contact Florestone Products to verify product specifications.

Dimensions may vary $\pm \frac{1}{4}$ inch. Please check unit before installation.

For barrier-free installation, contractor shall provide 5/8" minimum recess for curb in sub floor.

ADA compliance when accessories installed by manufacturer. **Note: Exterior floor drain for water run-off recommended.**Symmons® is a Registered Trade Mark of Symmons Industries, Inc.
Moen® is a Registered Trade Mark of Moen Corporation.

Florestone Model 3PC-39-62H Barrier-Free Shower

 $\begin{array}{l} \text{O.D.} = 62\text{" x } 39\text{" x } 77\text{"} \\ \text{I.D.} = 60\text{" x } 37\text{" x } 76\text{"} \\ \text{Weight: } 295\text{ lbs.} \end{array}$

Architect's Specifications

Furnish and install three-piece gel-coated fiberglass shower stall Model 3PC-39-62H designed for barrier-free use as manufactured by Florestone Products Company. Basic shower will conform to ANSI-Z-124.2 and the accessorized module to ANSI-A-117.1. Unit to include stainless steel curtain rod; Symmons® pressure balance mixing valve with concealed check stops; Moen® hand-held shower head with hose and stainless steel slide bar/grab bar; stainless steel wrap-around grab bar; stainless steel recessed soap dish.

Supplied with 2" brass drain.

Shower curtain optional.

Curtain Size: 72" x 72".

Standard Color: White.

Special order colors available.

Standards:

I.A.P.M.O. File No. 0687 ANSI-Z-124.2 & ANSI-A-117.1





FLORESTONE PRODUCTS CO., INC.

2851 Falcon Drive • Madera, CA 93637

T. 559.661.4171 • T. 800.446.8827

F. 559.661.2070 • florestone.com