





## Dimensions subject to change without notice.

Contact Florestone Products to verify product specifications.

# Dimensions may vary $\pm \frac{1}{4}$ " inch. Please check unit before installation.

For barrier-free installation, contractor shall provide 5/8" minimum recess for curb in sub floor.

ADA compliance when accessories installed by manufacturer. **Note: Exterior floor drain for water run-off recommended.** Symmons<sup>®</sup> is a Registered Trade Mark of Symmons Industries, Inc. Moen<sup>®</sup> is a Registered Trade Mark of Moen Corporation.

### Florestone Model 3PC-39-62H Barrier-Free Shower

 $\begin{array}{l} \text{O.D.} = 62"\,x\,39"\,x\,77"\\ \text{I.D.} = 60"\,x\,37"\,x\,76"\\ \text{Weight:}\,295 \,\text{Ibs.} \end{array}$ 

# Architect's Specifications

Furnish and install three-piece gel-coated fiberglass shower stall Model 3PC-39-62H designed for barrier-free use as manufactured by Florestone Products Company. Basic shower will conform to ANSI-Z-124.2. Unit to include stainless steel curtain rod; Symmons<sup>®</sup> pressure balance mixing valve with concealed check stops; Moen<sup>®</sup> hand-held shower head with hose and chrome-plated slide bar; stainless steel wrap-around grab bar; stainless steel recessed soap dish.

Supplied with 2" brass drain.

Shower curtain optional.

Curtain Size: 72" x 72".

Standard Color: White.

Special order colors available.

#### Standards:

I.A.P.M.O. File No. 0687 ANSI-Z-124.2



### FLORESTONE A Spec Above.

## FLORESTONE PRODUCTS CO., INC.

2851 Falcon Drive • Madera, CA 93637
Т. 559.661.4171 • Т. 800.446.8827
F. 559.661.2070 • florestone.com